

# Mussell Wheels

STD = Standard Gear Ring

T = Tapered Gear Ring

D.C. = Deep Cut Gear Ring

All Other Standard Geared Wheel Clearances With Standard Square Bar Rail or Standard A.S.C.E. Rail (up to 85 Lbs.) = 1/32" Clear.

All Rail Based Upon Use with Standard Rail Hook Bolts.

All Rail Based upon Splice Plate Clearance.

## MUSSELL CRANE MFG.





620-B Wellington Avenue,  
P.O. Box 253, Station Main,  
Chilliwack, B.C. Canada  
V2P 6J1  
Phone: 604-792-5023  
Fax: 604-792-5038  
Email: info@mussellcrane.com

*"Proudly Canadian"*

## RAIL SIZE & GEAR RING TO SPLICE PLATE CHART FOR CUSTOM DOUBLE FLANGE GEARED WHEELS

253 CUSTOM FLANGE GEARED WHEELS			
	STD	T	D.C.
40-Lb. A.S.C.E.	1/32"	1/8"	-
60-Lb. A.S.C.E.	1/32"	1/8"	-
80-Lb. A.S.C.E.	1/32"	1/8"	-

363 CUSTOM FLANGE GEARED WHEELS			
	STD	T	D.C.
60-Lb. A.S.C.E.	1/32"	1/8"	1/4"
80-Lb. A.S.C.E.	1/32"	1/8"	1/4"
85-Lb. A.S.C.E.	1/32"	1/8"	5/16"
100-Lb. A.S.C.E.	1/8"	1/8"	3/8"
85-Lb. C.P.	1/32"	1/8"	5/16"
100-Lb. A.R.A.-A	-	-	3/16"
100-Lb. A.R.A.-A.H.F.	1/8"	1/8"	5/16"
100-Lb. A.R.E.A.H.F.	3/16"	3/16"	3/16"
100-Lb. A.R.E.A.	-	-	1/8"
100-Lb. A.R.A.-B	-	-	3/16"
105-Lb. - N.Y.C.	-	-	3/16"
110-Lb. A.R.E.A.	-	-	3/16"
112-Lb. A.R.E.A.	1/8"	3/16"	1/4"
115-Lb. A.R.E.A.	3/16"	3/16"	5/16"
132-Lb. A.R.E.A.	3/16"	3/16"	1/4"
136-Lb. A.R.E.A.	1/4"	1/4"	5/16"



Above Rail Based Upon Splice Plate Clearance.