



Mussell Wheels

All Standard Wheel Clearances With Standard Square Bar Rail or Standard A.S.C.E. Rail (up to 85 Lbs.) = 1/32" Clear.

Refer to Rail Size & Gear Ring to Splice Plate Chart (Custom Double Flange Geared Wheels) For Other Available Clearances.

All A.S.C.E. Rail Based Upon Use with Standard A.S.C.E. Rail Hook Bolts.

MUSSELL CRANE MFG.

620-B Wellington Avenue,
P.O. Box 253, Station Main,
Chilliwack, B.C. Canada
V2P 6J1

Phone: 604-792-5023

Fax: 604-792-5038

Email: info@mussellcrane.com

"Proudly Canadian"

RAIL SIZE CHART FOR STANDARD DOUBLE FLANGE WHEELS

Standard Wheel Diameter	STANDARD SQUARE BAR RAIL (inches)							
	1"	1¼"	1½"	1¾"	2"	2¼"	2½"	3"
120 mm	✓	✓	✓					
153 mm		✓	✓	✓	✓			
253 mm			✓	✓	✓	✓	✓	
363 mm				✓	✓	✓	✓	✓



Standard Wheel Diameter	STANDARD A.S.C.E. RAIL (pounds)							
	16	20	25	30	40	60	80	85
120 mm	✓	✓	✓					
153 mm			✓	✓	✓			
253 mm					✓	✓	✓	
363 mm						✓	✓	✓

